

(Translation)

Japanese Unexamined Utility Model Application

Publication No. 49-107081

Publication Date: September 12, 1974

Title of Invention

Trolley Conveyor

What is claimed is:

A trolley conveyor comprising:

a load carrier 3 including a plurality of front trolleys 1 and a plurality of rear trolleys 2 located at suitable intervals in a transfer direction to be pivotally supported, respectively, around vertical axes a, b to be capable of rotating;

paralleled path sections 4a, 4b located at a midway of a transfer conveyor path 4 of the load carrier 3, and moving the front and rear trolleys 1, 2 individually to transfer the load carrier 3 in a position at a right angle or a substantially right angle with respect to the transfer direction, wherein

in order for sending out the load carrier 3 that has reached a vicinity of terminal ends of the paralleled path sections 4a, 4b, in a direction opposite to a direction of moving in these paralleled path sections 4a, 4b,

the trolley conveyor further comprises:

paralleled path sections 4a', 4b' located between a vicinity of start ends of the paralleled path sections 4a, 4b and a conveyor path 4A to which the load carrier 3 is sent out, such that the paralleled path sections 4a', 4b' are inclined toward the conveyor path 4A with respect to the transfer direction and are brought to

THIS PAGE BLANK (USPTO)

be parallel to each other at an interval l smaller than a relative interval L between the paralleled path sections 4a, 4b; and

bent path sections 4c, 4d located at a transfer path section from the wide paralleled path sections 4a, 4b to the narrow inclined paralleled path sections 4a', 4b' and at a transfer path section from the narrow inclined paralleled sections 4a', 4b' to the conveyor path 4A, such that the load carrier 3 is turned at each transfer path section by 90 degrees with respect to a substantial one point as a center O.

THIS PAGE BLANK (USPTO)

45013

⑤日本分類

83(5)E 0

①日本国特許庁

公開実用新案公報

①実開昭49-107081

庁内整理番号 6729-38

④公開 昭49(1974). 9-12

審査請求 未請求 (全3頁)

⑦トロリーコンベヤ装置

②実 願 昭48-6845

②出 願 昭48(1973)1月11日

⑦考 案 者 清水悟

大阪市西淀川区御幣島3の2の
11大福機工株式会社内

⑦出 願 人 大福機工株式会社

大阪市西淀川区御幣島3の2の
11

⑦代 理 人 弁理士 藤田辰之丞 外2名

⑤実用新案登録請求の範囲


移送方向に适当間隔を隔てて前後に複数のトロリー1, 2を夫々縦軸芯a, bの周りに回動自在に枢支保持させてある物品搬送具3の移送コンベヤ経路4途中に、前記前後のトロリー1, 2を各別に移行させることにより、物品搬送具3を移送方向に対して直角又は略直角に姿勢させて移送させる平行経路部分4a, 4bを形成し、この平行経路部分4a, 4bの終端近傍部に達した物品搬送具3を、この平行経路部分4a, 4bへの移入

方向とは反対方向に送り出すにあつて、前記平行経路部分4a, 4bの紙端近傍部と物品搬送具3が送り出されるべきコンベヤ経路4Aとの間に、平行経路部分4a, 4bでの移送方向に対してコンベヤ経路4A側に傾斜しかつ、平行経路部分4a, 4bの相对間隔Lよりも小なる間隔L'で互いに平行な傾斜平行経路部分4a', 4b'を形成し、前記広軌平行経路部分4a, 4bから狭軌傾斜平行経路部分4a', 4b'への移行経路箇所ならびに狭軌傾斜平行経路部分4a', 4b'からコンベヤ経路4Aへの移行経路箇所と夫々、物品搬送具3を略一点を中心0にして90度方向転換させる屈曲経路部分4c, 4dを形成してあることを特徴とするトロリーコンベヤ装置。


図面の簡単な説明

図面は本考案に係るトロリーコンベヤ装置の実施の態様を例示し、第1図はトロリーコンベヤのレイアウト、第2図は要部の側面図、第3図は動作説明図である。3……物品搬送具、4a, 4b……平行経路部分、4a', 4b'……傾斜平行経路部分、4c, 4d……屈曲経路部分。


第1図



第2図



第3図



THIS PAGE BLANK (USPTO)